

YE-UL18
METRIC



YG INDEXABLE CUTTING TOOLS



YG-1 CO., LTD.

HEAD OFFICE

211, Sewolcheon-ro, Bupyeong-gu, Incheon, South Korea

Phone : +82-32-526-0909

E-mail : yg1@yg1.kr

www.yg1.kr

Note The new address above has currently been updated to the new Korean postal standard valid since 2014.
Notice that the physical Head Office location did NOT change.



Search 'YG-1' on social media outlets

YG1YEUL180518002

YG-1 CO., LTD.

Tool specifications are subject to change without prior notice.

INDEX

Turning

Insert ISO Code System		p. 04
Product Overview	Turning Grades	p. 06
	Turning Chipbreakers	p. 08
Turning Inserts		p. 12

Parting & Groove Turn

Parting & Groove Turn	Overview / Inserts	p. 34
-----------------------	--------------------	-------

Milling

Code Keys	Milling Cutters / Code System	p. 37
Product Overview	Cutters / Inserts Overview / Grades / Chipbreakers	p. 40
Milling Inserts		p. 44
Milling Cutters		
• Shoulder Milling Cutters (90°)	APKT 10, 16 / APMT 11, 16	p. 45 / p. 47
• Face Milling Cutters (43, 45°)	ODMT 06 / SEKT 12	p. 51 / p. 63
• Copy Milling Cutters (Round)	RDKT 08, 10, 12	p. 55

Drilling

Product Overview	Drilling Grades / Inserts / Chipbreakers	p. 68
Drilling Inserts		p. 69

Comparison Chart

Turning Grades	p. 72
Turning Chipbreakers	p. 73



Turning - Name Code System

Insert ISO Code System


*Metric

1	2	3	4	5	6	7	8	9
C	N	M	G	12	04	08	-UG	YG3020
Shape	Clearance	Tolerance	Clamping & Chipbreaker	Insert Size	Insert Thickness	Corner Radius	Chipbreaker Geometry	Grade

page 8

1 - Shape

Symbol	Shape	
H	Hexagonal	
O	Octagonal	
P	Pentagonal	
S	Square	
T	Triangular	
C	Rhombic 80°	
D	Rhombic 55°	
V	Rhombic 35°	
W	Trigon	
L	Rectangular	
K	Parallelogram 55°	
R	Round	



3 - Tolerance Class

Symbol	Inner Circle IC (mm)	Nose Height M (mm)	Thickness S (mm)
E	±0.025	±0.025	±0.025
G	±0.025	±0.025	±0.13
K	±0.05~0.15	±0.013	±0.025
M	±0.05~0.15	±0.08~0.2	±0.13
U	±0.08~0.25	±0.13~0.38	±0.13

4 - Clamping & Chipbreaker

Symbol	Clamping	Chipbreaker	Figure
N	No clamping hole	X	
R		One Face	
A	Cylindrical Clamping hole	X	
M		One Face	
G		Both Faces	
W	Screw Hole	X	
T		One Face	
U		Both Faces	
X	Special		

2 - Relief Angle (AN)

Symbol	Relief Angle (AN)	
N	No Relief Angle	
C	Relief 7°	
P	Relief 11°	
D	Relief 15°	
E	Relief 20°	
F	Relief 25°	
O	Special	



*Inch

1	2	3	4	5	6	7	8	9
C	N	M	G	4	3	2	-UG	YG3020
Shape	Clearance	Tolerance	Clamping & Chipbreaker	Insert Size	Insert Thickness	Corner Radius	Chipbreaker Geometry	Grade

page 8

5 - Insert Size

Metric							Inner Circle IC (mm)	Inch
06	11	06	07	11			6.35	2
07							7.94	2.5
09	16	09	11	16	06	09 (00)	9.525	3
12	22	12	15	22	08	12 (00)	12.7	4
15		16					15.875	5
		19					19.05	6
						06 (M0)	6	
						08 (M0)	8	
						10 (M0)	10	
						12 (M0)	12	
						16 (M0)	16	



6 - Insert Thickness (S)

Metric	Thickness - S (mm)	Inch
T1	1.98	1.2
02	2.38	1.5
03	3.18	2
T3	3.97	2.5
04	4.76	3
05	5.56	3.5
06	6.35	4
07	7.94	5

7 - Corner Radius (RE)


Metric	Corner Radius - RE (mm)	Inch
01	0.1	0
02	0.2	0.5
04	0.4	1
08	0.8	2
12	1.2	3
16	1.6	4
20	2.0	5
24	2.4	6

Turning Grades

Turning Grades		P Steel				M Stainless Steel				K Cast Iron				N Non Ferrous			
		P05	P15	P25	P35	M05	M15	M25	M35	K05	K15	K25	K35	N05	N15	N25	N35
CVD	YG1001	1001								1001							
	YG3010		3010								3010						
	YG3020			3020													
	YG3030				3030			3030									
PVD	YG801		801			801											
DLC	YG100														100		
Uncoated	YG10														10		

YG1001 P01 - P10 K10 - K25	CVD TiCN - Al ₂ O ₃ 	First choice for stable machining of cast iron - Substrate especially designed for high wear resistance - Thick Al₂O₃ layer ensures good wear resistance at high cutting speeds including dry machining
YG3010 P05 - P20 K15 - K35	CVD TiCN - Al ₂ O ₃ 	First choice for Finishing Steels, and Ductile Cast iron - Finishing and light machining of steel under in stable condition - New Al₂O₃ coating technology and excellent surface smoothness increases wear resistance and chipping resistance
YG3020 P15 - P30	CVD TiCN - Al ₂ O ₃ 	First Choice grade for general Steel application - Substrate especially designed for good toughness - Excellent surface smoothness increases wear resistance and reliability
YG3030 P20 - P35 M20 - M35	CVD TiCN - Al ₂ O ₃ 	Interrupted cutting of steel and stainless steel - Substrate for heavy roughing in mild steel and low carbon alloy steel - New Al₂O₃ technology and optimized surface treatment achieves a good balance between wear resistance and chipping resistance
YG801 P10 - P30 S05 - S25 M05 - M25 H20 - H40	PVD - TiAlN 	Universal Grade for mid and low cutting conditions - Recommended for mild steel, stainless steel, and boring application - Substrate and special PVD coating for excellent wear resistance
YG100 N05 - N35	DLC 	First Choice grade for aluminum with DLC coating - Submicron carbide for high wear resistance - DLC coating minimizes Built Up Edge tendency. - Improves tool life in sticky non-ferrous alloy
YG10 N05 - N35	Uncoated 	Uncoated Grade for General Aluminum - Substrate consisted of submicron carbide for high wear resistance - Shining surface to prevent built up edge







Turning Grade Map



Recommended Cutting Conditions




Cutting Speed			Vc (m/min.)											
ISO	VDI	Sub Group	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10					
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-

Turning Chipbreakers - Negative






				Feed							Fn (mm/rev.)			
P	M	K	N	0 0.1 0.2 0.3 0.4 0.5 0.6										
P				UF 	Finishing 	Fn 0.05~0.2								
	Ap 0.5~1.5													
P				UL 	Semi Finishing and sticky materials 	Fn 0.05~0.3								
	Ap 1~3													
P				UM 	For Medium & Unstable conditions 	Fn 0.15~0.35								
	Ap 1~3													
P				UG 	First Choice for Medium (Stable application) 	Fn 0.25~0.4								
	Ap 1.5~4													
P		K		UC 	Medium Roughing and First choice for Cast Iron 	Fn 0.25~0.5								
	Ap 1.5~4													
P		K		UR 	Roughing and Heavy interrupted cut 	Fn 0.3~0.6								
	Ap 2~6													
	M			MM 	Stainless Steel Medium 	Fn 0.15~0.35								
Ap 1~3.5														
		K		..MA 	Cast Iron Heavy roughing 	Fn 0.2~0.6								
Ap 1~7														
				Depth of Cut										
				Ap (mm)										

Turning Chipbreakers - Negative


		Finishing	Semi Finishing	Medium	Medium Roughing	Roughing
P Steel	Stable					
	General					
	Unstable					
M Stainless Steel	Stable					
	General					
	Unstable					
K Cast Iron	Stable					
	General					
	Unstable					



Turning Chipbreakers - Positive



Turning Chipbreakers - Positive



Turning Inserts Overview


Negative Inserts

C		CNMA	12	16	19	p. 13
		CNMG	12		19	
D		DNMA		1506		p. 15
		DNMG	1504	1506		
K		KNUX	16			p. 17
S		SNMA	12			p. 18
		SNMG	12			
T		TNMA	16			p. 20
		TNMG	16	22		
		TNUX	16			p. 22
V		VNMG	16			p. 23
W		WNMA		08		p. 24
		WNMG	06	08		

Positive Inserts

C		CCGT		09		p. 26
		CCMT	06	09	12	
D		DCGT		11		p. 27
		DCMT	07	11		
R		RCMT	06	08	10	p. 28
S		SCMT	09	12		p. 29
T		TCGT		16		p. 30
		TCMT	11	16		
V		VBMT	16			p. 31
		VCMT / VCGT	16			p. 32

Turning - Inserts - Negative
CNMG / CNMA (80° Negative)




Series	L	IC	S
CNM□ 1204	12	12.7	4.76
CNM□ 1606	16	15.88	6.35
CNM□ 1906	19	19.05	6.35

● : Stock item ○ : Order made item

CNMA CNMG	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
..MA 	CNMA 120404	0.4	0.15~0.35	0.5~2.5	●	○					
	CNMA 120408	0.8	0.2~0.4	1~3.5	●	○					
	CNMA 120412	1.2	0.2~0.5	1.5~5	●	○					
	CNMA 160612	1.2	0.3~0.5	1.5~5	●	○					
	CNMA 160616	1.6	0.3~0.6	1.5~6	●	●					
	CNMA 190616	1.6	0.3~0.6	1.5~8	●	●					
-UF 	CNMG 120404 - UF	0.4	0.05~0.2	0.5~1.5		●	●	●	●		
	CNMG 120408 - UF	0.8	0.1~0.25	1~2.5		●	●	●			
-UL 	CNMG 120404 - UL	0.4	0.05~0.25	0.5~2		●	●				
	CNMG 120408 - UL	0.8	0.1~0.3	1~3		●	●	●			
	CNMG 120412 - UL	1.2	0.1~0.3	1.5~3.5		○	○	○			
-UM 	CNMG 120404 - UM	0.4	0.15~0.25	0.5~1.5		●	●	●			
	CNMG 120408 - UM	0.8	0.15~0.3	0.5~2	●	●	●	●			

Cutting Speed			Vc (m/min.)											
ISO	VDI	Sub Group	YG1001 Min. Max.	YG3010 Min. Max.	YG3020 Min. Max.	YG3030 Min. Max.	YG801 Min. Max.	YG100 Min. Max.	YG10 Min. Max.					
P	1~5	Non Alloy Steel	220 480	170 450	180 380	150 350	120 250	- -	- -					
	6~9	Low Alloy Steel	220 420	180 380	110 350	90 300	70 230	- -	- -					
	10~11	High Alloy Steel	- -	100 330	60 300	70 250	70 180	- -	- -					
M	12~13	Ferritic & Martensitic	- -	- -	- -	120 220	60 180	- -	- -					
	14	Austenitic Stainless Steel	- -	- -	- -	50 180	60 150	- -	- -					
K	15~16	Grey Cast Iron	170 420	120 300	- -	- -	60 160	- -	- -					
	17~18	Nodular Cast Iron	120 410	120 280	- -	- -	60 120	- -	- -					
N	21~30	Aluminum	- -	- -	- -	- -	- -	350 1200	250 800					
S	31~37	Heat Resistant Super Alloy	- -	- -	- -	35 80	35 60	- -	- -					
H	38~41	Hardened Material	- -	- -	- -	- -	40 80	- -	- -					

Turning - Inserts - Negative CNMG / CNMA (80° Negative)




Series	L	IC	S
CNM□ 1204	12	12.7	4.76
CNM□ 1606	16	15.88	6.35
CNM□ 1906	19	19.05	6.35

● : Stock item ○ : Order made item

CNMA CNMG	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
-UG  Medium Machining at stable condition	CNMG 120404 - UG	0.4	0.2~0.3	0.5~2		●	●	●			
	CNMG 120408 - UG	0.8	0.2~0.4	1~3	●	●	●	●	●		
	CNMG 120412 - UG	1.2	0.2~0.45	1.5~4		●	●	●			
-UC  Cast Iron and Medium roughing	CNMG 120404 - UC	0.4	0.25~0.35	0.5~2.5	●	●	●	●			
	CNMG 120408 - UC	0.8	0.25~0.45	1~4	●	●	●	●			
	CNMG 120412 - UC	1.2	0.3~0.55	1.5~4.5	●	●	●	●			
-UR  Roughing	CNMG 120408 - UR	0.8	0.25~0.55	1~4		●	●	●			
	CNMG 120412 - UR	1.2	0.3~0.6	1.5~5		●	●	●	●		
	CNMG 190612 - UR	1.2	0.3~0.6	1.5~6	●	●					
-MM  Stainless Steel Medium	CNMG 120408 - MM	0.8	0.2~0.35	1~3.5			○	●	●		

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Negative DNMG / DNMA (55° Negative)




Series	L	IC	S
DNM□ 1504	14	12.7	4.76
DNM□ 1506	14	12.7	6.35

● : Stock item ○ : Order made item

DNMA DNMG	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
..MA  Cast Iron	DNMA 150608	0.8	0.15~0.35	1~3	●						
	DNMA 150612	1.2	0.25~0.45	1.5~4	●						
-UF  Finishing	DNMG 150404 - UF	0.4	0.05~0.15	0.5~1.5		●	●	●	●		
	DNMG 150604 - UF	0.4	0.05~0.2	1~2		●	●	●	●		
	DNMG 150608 - UF	0.8	0.1~0.25	1.5~3.5		●	●	●			
-UL  Light Machining and Sticky Material	DNMG 150604 - UL	0.4	0.05~0.25	0.5~2		●	●				
	DNMG 150608 - UL	0.8	0.15~0.3	1.5~3		●	●	●			
-UM  Medium Machining Unstable condition	DNMG 150608 - UM	0.8	0.15~0.35	0.5~2		●	●	●			


Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Negative DNMG / DNMA (55° Negative)




Series	L	IC	S
DNM□ 1504	14	12.7	4.76
DNM□ 1506	14	12.7	6.35

● : Stock item ○ : Order made item

DNMA DNMG	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
-UG  Medium Machining at stable condition	DNMG 150408 - UG	0.8	0.2~0.35	1~2.5	●	●	●	●	●		
	DNMG 150604 - UG	0.4	0.2~0.3	0.5~2		●	●	●			
	DNMG 150608 - UG	0.8	0.2~0.35	1~3	●	●	●	●	●		
	DNMG 150612 - UG	1.2	0.2~0.4	1.5~3.5	●	●	●	●			
-UC  Cast Iron and Medium roughing	DNMG 150608 - UC	0.8	0.25~0.4	1~3	●	●	●	●			
	DNMG 150612 - UC	1.2	0.25~0.45	1.5~3.5	●	●	●	●			
-UR  Roughing	DNMG 150612 - UR	1.2	0.3~0.5	1.5~4		●	●	●	●		

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Negative KNUX (55° - 2 Corners Single Side)




Series	LE	S
KNUX 1604	15	4.76

● : Stock item ○ : Order made item

KNUX	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
..UX Left 	KNUX 160405 L	0.5	0.1~0.4	0.5~6		○	●	●	●		
..UX Right 	KNUX 160405 R	0.5	0.1~0.4	0.5~6		○	●	●	●		

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Negative SNMG / SNMA (90° Negative)




Series	IC	S
SNM□ 1204	12.7	4.76

● : Stock item ○ : Order made item

SNMA SNMG	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
..MA  Cast Iron	SNMA 120408	0.8	0.2~0.4	1~3.5	●						
	SNMA 120412	1.2	0.2~0.5	1.5~5	●						
-UF  Finishing	SNMG 120404 - UF	0.4	0.05~0.2	0.5~1.5					●		
-UL  Light Machining and sticky material	SNMG 120408 - UL	0.8	0.1~0.3	1~3		●	●	●			

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Negative SNMG / SNMA (90° Negative)




Series	IC	S
SNM□ 1204	12.7	4.76

● : Stock item ○ : Order made item

SNMA SNMG	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
-UG  Medium Machining at stable condition	SNMG 120408 - UG	0.8	0.2~0.4	1~3		●	●	●	●		
	SNMG 120412 - UG	1.2	0.2~0.45	1.5~4		●	●	●			
-UC  Cast Iron and Medium roughing	SNMG 120408 - UC	0.8	0.25~0.45	1~4	●	●	●	●			
	SNMG 120412 - UC	1.2	0.3~0.55	1.5~4.5	●						
-UR  Roughing	SNMG 120408 - UR	0.8	0.3~0.55	1~4.5		●	●	●			
	SNMG 120412 - UR	1.2	0.3~0.6	1.5~5			○	●	●		

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Negative TNMG / TNMA (60° Negative)




Series	L	IC	S
TN□□ 1604	15.7	9.53	4.76
TN□□ 2204	21	12.7	4.76

● : Stock item ○ : Order made item

TNMA TNMG	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
..MA Cast Iron	TNMA 160408	0.8	0.15~0.35	1~3	●						
	TNMA 160412	1.2	0.25~0.45	1.5~4	●						
-UF Finishing	TNMG 160404 - UF	0.4	0.05~0.2	1~2		●	●	●	●		
	TNMG 160408 - UF	0.8	0.1~0.25	1.5~3.5		●	●	●			
	TNMG 220404 - UF	0.4	0.05~0.2	1~4		●			●		
-UL Light Machining and sticky material	TNMG 160408 - UL	0.8	0.1~0.25	1.5~3.5		●	●	●			
-UM Medium Machining Unstable condition	TNMG 160408 - UM	0.8	0.15~0.35	0.5~2		●	●	●			

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Negative TNMG / TNMA (60° Negative)




Series	L	IC	S
TN□□ 1604	15.7	9.53	4.76
TN□□ 2204	21	12.7	4.76

● : Stock item ○ : Order made item

TNMA TNMG	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
-UG Medium Machining at Stable condition	TNMG 160404 - UG	0.4	0.2~0.3	0.5~2	●	●	●	●			
	TNMG 160408 - UG	0.8	0.2~0.35	1~3	●	●	●	●	●		
	TNMG 220408 - UG	0.8	0.2~0.3	1~4		●	●	●	●		
-UC Cast Iron and Medium roughing	TNMG 160404 - UC	0.4	0.25~0.4	0.5~2.5	○	●	●	●			
	TNMG 160408 - UC	0.8	0.25~0.4	1~3	●	●	●	●			
	TNMG 160412 - UC	1.2	0.25~0.45	1.5~3.5	●						
-UR Roughing	TNMG 160412 - UR	1.2	0.3~0.5	1.5~3		○	○	●	●		
	TNMG 220412 - UR	1.2	0.3~0.5	1.5~4	●	○	○	●	●		
	TNMG 220416 - UR	1.6	0.3~0.5	1.5~6	●	●					

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Negative TNUX (60° Negative)




Series	LE	IC	S
TNUX 1604	9.4	9.53	4.76

● : Stock item ○ : Order made item

TNUX	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
..UX Left	TNUX 160404 L	0.4	0.1~0.3	0.5~4		○	●		●		
	TNUX 160408 L	0.8	0.1~0.4	0.5~6		○	●		●		
..UX Right	TNUX 160404 R	0.4	0.1~0.3	0.5~4		○	●		●		
	TNUX 160408 R	0.8	0.1~0.4	0.5~6		○	●		●		

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Negative VNMG (35° Negative)




Series	L	IC	S
VNMG 1604	15.8	9.53	4.76

● : Stock item ○ : Order made item

VNMG	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
..MA Cast Iron	VNMA 160408	0.8	0.15~0.35	1~3	●						
-UF Finishing	VNMG 160404 - UF	0.4	0.05~0.15	0.5~2		●	●	●	●		
	VNMG 160408 - UF	0.8	0.05~0.25	1~2.5		●	●	●			
-UL Medium Machining and sticky material	VNMG 160408 - UL	0.8	0.1~0.25	1~2.5		○	●				
-UG Medium Machining at stable condition	VNMG 160408 - UG	0.8	0.2~0.3	1~3	●	●	●	●	●		
-UC Cast Iron and Medium roughing	VNMG 160404 - UC	0.4	0.25~0.4	0.5~2.5		●					
	VNMG 160408 - UC	0.8	0.25~0.4	1~3	●	●	●	●			
-UR Roughing	VNMG 160412 - UR	1.2	0.25~0.35	1.2~3		○	○	●	●		

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Negative WNMG / WNMA (80° Trigonal Negative)




Series	L	IC	S
WNM□0604	5.7	9.53	4.76
WNM□0804	7.8	12.7	4.76

● : Stock item ○ : Order made item

WNMA WNMG	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
..MA Cast Iron	WNMA 080404	0.4	0.15~0.35	0.5~2.5	●						
	WNMA 080408	0.8	0.2~0.4	1~3.5	●	○					
	WNMA 080412	1.2	0.2~0.5	1.5~5	●	○					
-UF Finishing	WNMG 060404 - UF	0.4	0.05~0.2	0.5~1.5		●	●	○	●		
	WNMG 080404 - UF	0.4	0.05~0.2	0.5~2		●	●	●	●		
	WNMG 080408 - UF	0.8	0.1~0.25	1~2.5		●	●	●			
-UL Light Machining and sticky material	WNMG 060408 - UL	0.8	0.1~0.3	1~2.5		●	●	○			
	WNMG 080408 - UL	0.8	0.1~0.3	1~3		●	●	●			

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Negative WNMG / WNMA (80° Trigonal Negative)




Series	L	IC	S
WNM□0604	5.7	9.53	4.76
WNM□0804	7.8	12.7	4.76

● : Stock item ○ : Order made item

WNMA WNMG	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
-UM Medium Machining at unstable condition	WNMG 080408 - UM	0.8	0.15~0.3	0.5~2	●	●	●	●			
-UG Medium Machining at stable condition	WNMG 060408 - UG	0.8	0.2~0.4	1~2.5			●		●		
	WNMG 080404 - UG	0.4	0.2~0.3	1.5~2.5		●	●	●			
	WNMG 080408 - UG	0.8	0.2~0.4	1~3.5	●	●	●	●	●		
	WNMG 080412 - UG	1.2	0.2~0.4	1~3.5	●						
-UC Cast Iron and Medium roughing	WNMG 080404 - UC	0.4	0.25~0.4	0.5~3.5	●	●	●	●			
	WNMG 080408 - UC	0.8	0.25~0.45	1~4	●	●	●	●			
	WNMG 080412 - UC	1.2	0.3~0.55	1.5~4.5	●	●	●	●			
-UR Roughing	WNMG 080408 - UR	0.8	0.3~0.6	1~4.5		●	●	●			
	WNMG 080412 - UR	1.2	0.3~0.6	1.5~5	●	○	○	●	●		
	WNMG 080416 - UR	1.6	0.3~0.6	1.5~5	●	●					

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Positive CCMT / CCGT (80° Positive)




Series	L	IC	S
CCMT 0602	6.2	6.35	2.38
CCMT 09T3	9.2	9.53	3.97
CCMT 1204	12.4	12.7	4.76

● : Stock item ○ : Order made item

CCGT CCMT	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
-AL Aluminum	CCGT 09T302 - AL	0.2	0.02~0.08	0.5~1						●	●
	CCGT 09T304 - AL	0.4	0.05~0.25	0.5~2						●	●
	CCGT 09T308 - AL	0.8	0.1~0.35	1~3						●	●
-UF Finishing	CCMT 060204 - UF	0.4	0.05~0.15	0.5~1.5		●	●				
	CCMT 09T304 - UF	0.4	0.05~0.2	0.5~2		●	●				
-UG General	CCMT 060204 - UG	0.4	0.15~0.25	0.5~2					●		
	CCMT 060208 - UG	0.8	0.15~0.25	0.8~2		●			●		
	CCMT 09T304 - UG	0.4	0.15~0.2	0.5~2		●	●		●		
	CCMT 09T308 - UG	0.8	0.15~0.3	0.8~2.5		●	●		●		
	CCMT 120404 - UG	0.4	0.2~0.25	0.5~2.5		●	●				
	CCMT 120408 - UG	0.8	0.2~0.35	0.8~3.5		●	●	●	●		

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Positive DCMT / DCGT (55° Positive)




Series	L	IC	S
DCMT 0702	7.5	6.35	2.38
DCMT 11T3	11.2	9.53	3.97

● : Stock item ○ : Order made item

DCGT DCMT	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
-AL Aluminum	DCGT 11T302 - AL	0.2	0.02~0.08	0.5~1						●	●
	DCGT 11T304 - AL	0.4	0.05~0.25	0.5~2						●	●
	DCGT 11T308 - AL	0.8	0.1~0.3	1~2.5						●	●
-UF Finishing	DCMT 070204 - UF	0.4	0.05~0.15	0.5~1.5		●	●				
	DCMT 11T304 - UF	0.4	0.05~0.2	0.5~2		●	●				
	DCMT 11T308 - UF	0.8	0.05~0.25	1~2.5		●	●				
-UG General	DCMT 070204 - UG	0.4	0.15~0.25	0.5~1.5		●	●		○		
	DCMT 070208 - UG	0.8	0.15~0.25	0.8~1.5		●					
	DCMT 11T304 - UG	0.4	0.15~0.25	0.5~2		●	●		●		
	DCMT 11T308 - UG	0.8	0.2~0.35	0.8~2.5		●	●	○	●		

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Positive RCMT (Round Positive)




Series	INSD	S
RCMT 0602	6	2.38
RCMT 0803	8	3.18
RCMT 10T3	10	3.97
RCMT 1204	12	4.76

● : Stock item ○ : Order made item

RCMT	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
 General	RCMT 0602M0	3	0.05~0.25	0.2~1.2	○	○	●		●		
	RCMT 0803M0	4	0.05~0.3	0.5~1.5	○	○	●		●		
	RCMT 10T3M0	5	0.1~0.35	0.5~2.5	○	○	●		●		
	RCMT 1204M0	6	0.15~0.45	0.5~3	○	○	●		●		

Turning - Inserts - Positive SCMT (Square Positive)



Series	IC	S
SCMT 09T3	9.53	3.97
SCMT 1204	12.7	4.76


● : Stock item ○ : Order made item

SCMT	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
-UF  Finishing	SCMT 09T304 - UF	0.4	0.1~0.25	0.5~2		○	●				
-UG  General	SCMT 09T304 - UG	0.4	0.2~0.35	1~2.5	●				●		
	SCMT 09T308 - UG	0.8	0.2~0.35	1~2.5	●	●	●		●		
	SCMT 120408 - UG	0.8	0.2~0.4	1~3.5		●	●	○			

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Positive TCMT / TCGT (Triangle Positive)




Series	L	IC	S
TCMT 1102	10.3	6.35	2.38
TCMT 16T3	15.6	9.53	3.97

● : Stock item ○ : Order made item

TCGT TCMT	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
-AL Aluminum	TCGT 16T302 - AL	0.2	0.02~0.05	0.5~1						●	●
	TCGT 16T304 - AL	0.4	0.05~0.25	0.5~2						●	●
	TCGT 16T308 - AL	0.8	0.1~0.35	1~3						●	●
-UF Finishing	TCMT 110204 - UF	0.4	0.05~0.2	0.5~2		●	●				
	TCMT 16T304 - UF	0.4	0.05~0.25	0.5~3		●	●		●		
-UG General	TCMT 110204 - UG	0.4	0.15~0.25	0.5~2					●		
	TCMT 110208 - UG	0.8	0.15~0.25	0.8~2.5		●					
	TCMT 16T304 - UG	0.4	0.15~0.25	0.5~2		●	●				
	TCMT 16T308 - UG	0.8	0.2~0.35	0.8~3		●	●	○	●		

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Positive VBMT (35° Positive)




Series	L	IC	S
VBMT 1604	15.8	9.53	4.76

● : Stock item ○ : Order made item

VBMT	Designation	RE	Fn (mm/rev.)	Ap (mm)	YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
-UF Finishing	VBMT 160404 - UF	0.4	0.05~0.2	0.5~2		●	●				
	VBMT 160408 - UF	0.8	0.05~0.25	0.5~3		●	●				
-UG General	VBMT 160404 - UG	0.4	0.15~0.25	0.5~2.5		●	●		●		
	VBMT 160408 - UG	0.8	0.2~0.4	1~3		●	●	○	●		

Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

Turning - Inserts - Positive
VCMT / VCGT (35° Positive)



Series	L	IC	S
VCMT 1604	15.8	9.53	4.76

● : Stock item ○ : Order made item

	VCMT VCGT	Designation	RE	Fn (mm/rev.)	Ap (mm)							
						YG1001	YG3010	YG3020	YG3030	YG801	YG100	YG10
-AL	 Aluminum	VCMT 160402 - AL	0.2	0.02~0.05	0.5~1						●	●
		VCMT 160404 - AL	0.4	0.05~0.25	0.5~2						●	●
		VCMT 160408 - AL	0.8	0.1~0.35	1~3						●	●
-UF	 Finishing	VCMT 160404 - UF	0.4	0.05~0.25	0.5~3			●				
-UG	 General	VCMT 160404 - UG	0.4	0.15~0.25	0.5~2.5					●		
		VCMT 160408 - UG	0.8	0.2~0.4	1~3			●		●		


Cutting Speed			Vc (m/min.)													
ISO	VDI	Sub Group	YG1001		YG3010		YG3020		YG3030		YG801		YG100		YG10	
			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	220	480	170	450	180	380	150	350	120	250	-	-	-	-
	6~9	Low Alloy Steel	220	420	180	380	110	350	90	300	70	230	-	-	-	-
	10~11	High Alloy Steel	-	-	100	330	60	300	70	250	70	180	-	-	-	-
M	12~13	Ferritic & Martensitic	-	-	-	-	-	-	120	220	60	180	-	-	-	-
	14	Austenitic Stainless Steel	-	-	-	-	-	-	50	180	60	150	-	-	-	-
K	15~16	Grey Cast Iron	170	420	120	300	-	-	-	-	60	160	-	-	-	-
	17~18	Nodular Cast Iron	120	410	120	280	-	-	-	-	60	120	-	-	-	-
N	21~30	Aluminum	-	-	-	-	-	-	-	-	-	-	350	1200	250	800
S	31~37	Heat Resistant Super Alloy	-	-	-	-	-	-	35	80	35	60	-	-	-	-
H	38~41	Hardened Material	-	-	-	-	-	-	-	-	40	80	-	-	-	-

PARTING &
GROOVE TURN

Parting & Groove Turn Overview

Parting & Groove Turn Grades





Parting and Grooving Grades		P Steel				M Stainless Steel				K Cast Iron				S Super Alloy			
		P05	P15	P25	P35	M05	M15	M25	M35	K05	K15	K25	K35	S05	S15	S25	S35
PVD	YG602			602				602				602				602	

YG602 P20 - P35 M20 - M40 K20 - K40 S15 - S25	PVD - TiAlN		Universal grade for Parting & Groove Turn - Ultra Dense PVD Coating with optimal thermal resistance & strength - Sub-Micron substrate designed for demanding application

Parting & Groove Turn Inserts


	TD. Series	Inserts	2, 3, 4
		TDN TDP TDY	

Parting & Groove Turn Chipbreakers

-P TDP			• Parting & Grooving (Positive)
-N TDN			• Parting & Grooving (General)
-Y TDY			• Groove Turn

Parting & Groove Turn - Inserts
Parting & Groove Turn Inserts (TD.)



TD.		Designation	RE	Parting & Grooving		Groove Turn		YG602
				Fn (mm/rev.)	Tmax (mm)	Fn (mm/rev.)	Ap (mm)	
TDP  Parting & Grooving (Positive)		TDP 2002	0.2	0.04~0.12	19	-	-	●
		TDP 3002	0.2	0.05~0.16	19	-	-	●
		TDP 4003	0.3	0.06~0.18	19	-	-	●
TDN  Parting & Grooving (General)		TDN 2002	0.2	0.06~0.18	19	-	-	●
		TDN 3002	0.2	0.07~0.22	19	-	-	●
		TDN 4003	0.3	0.08~0.25	19	-	-	●
TDY  Groove Turn		TDY 3 E - 0.4	0.4	0.10~0.20	19	0.10~0.38	0.5~2.2	●
		TDY 4 E - 0.4	0.4	0.15~0.26	19	0.10~0.40	0.5~2.8	●



● : Stock item ○ : Order made item

Cutting Speed			Vc (m/min.)	
ISO	VDI	Sub Group	YG602	
			Min.	Max.
P	1~5	Non Alloy Steel	90	180
	6~9	Low Alloy Steel	80	120
	10~11	High Alloy Steel	80	110
M	12~13	Ferritic & Martensitic	70	160
	14	Austenitic Stainless Steel	55	140
K	15~16	Grey Cast Iron	110	185
	17~18	Nodular Cast Iron	110	140
N	21~30	Aluminum	250	440
S	31~37	Heat Resistant Super Alloy	25	45
H	38~41	Hardened Material	25	50

Code Keys - Milling Cutters



MILLING

Milling - Code System

Insert Code System


1 A Shape	2 P Relief Angle (AN)	3 K Tolerance	4 T Clamping & Chipbreaker	5 16 Insert Size	6 04 Insert Thickness (S)	7 08 CornerRadius
------------------------	------------------------------------	----------------------------	---	-------------------------------	--	--------------------------------

1 - Shape

Symbol	Shape	
H	Hexagonal	
O	Octagonal	
P	Pentagonal	
S	Square	
T	Triangular	
V	Rhombic 35°	
W	Trigon	
L	Rectangular	
A	Parallelogram 80°	
R	Round	

2 - Relief Angle (AN)

Symbol	Relief Angle (AN)	
N	No Relief Angle	
C	Relief 7°	
P	Relief 11°	
D	Relief 15°	
E	Relief 20°	
F	Relief 25°	
O	Special	



3 - Tolerance Class

Symbol	Inner Circle IC (mm)	Nose Height M (mm)	Thickness S (mm)
E	±0.025	±0.025	±0.025
G	±0.025	±0.025	±0.13
K	±0.05~0.15	±0.013	±0.025
M	±0.05~0.15	±0.08~0.2	±0.13
U	±0.08~0.25	±0.13~0.38	±0.13

4 - Clamping & Chipbreaker

Symbol	Clamping	Chipbreaker	Figure
N	No clamping hole	X	
R		One Face	
W	Screw Hole	X	
T		One Face	
U		Both Faces	
X	Special		

5 - Insert Size

* No Standard for milling insert size

6 - Insert Thickness


* No Standard for milling insert thickness

8 PDTR Corner Geometry	9 -TR Chipbreaker	10 YG602 Grade
-------------------------------------	--------------------------------	-----------------------------

7 - Corner Radius (RE)

Symbol	Corner Radius - RE (mm)	Symbol	Corner Radius - RE (mm)
04	0.4	16	1.6
08	0.8	20	2.0
12	1.2	24	2.4

8 - Corner Geometry



8-1 P Cutting Edge Angle (KRINS)	8-2 D Wiper Edge Clearance (AS)	8-3 T Edge Condition	8-4 R Feed Direction
---	--	-----------------------------------	-----------------------------------

*Refer to page. 43 for -AL, -ST, -TR... types

8-1 - Cutting Edge Angle (KRINS)

Symbol	Cutting Edge Angle (KRINS)
P	90°
A	45°
D	60°
E	75°
F	85°
Z	Special

8-2 - Wiper Edge Clearance (AS)

Symbol	Wiper Edge Clearance (AS)
N	0°
P	11°
D	15°
E	20°
F	25°
Z	Special





8-3 - Edge Condition

Symbol	Edge Condition	
F	Sharp	
E	Rounded	
T	Chamfered	
S	Chamfered and Rounded	

8-4 - Feed Direction


Symbol	Feed Direction	
R	Right-hand Insert	
N	Neutral Insert	
L	Left-hand Insert	

Milling Cutters Overview

Shoulder Mill		Diameter												Application
		Type	16	20	25	32	40	50	63	80	100	125	160	
 APKT 2 Corner 90° Positive (p. 45)	APKT 1003 (APMX 9mm)	CYL	●	●										
		WEL	●	●										
		SHL					●	●						
	APKT 1604 (APMX 14mm)	CYL			●	●								
		WEL			●	●								
		SHL						●	●	●				
 APMT 2 Corner 90° Positive (p. 47)	APMT 1135 (APMX 9mm)	CYL	●	●	●									
		WEL				●								
	APMT 1604 (APMX 14mm)	CYL			●									
		WEL				●								
		SHL						●	●	●				


Face Mill		Diameter												Application
		Type	16	20	25	32	40	50	63	80	100	125	160	
 ODMT 8 Corner 43° Positive (p. 51)	ODMT 0605 ODMW 0605 (APMX 3.5mm)	SHL							●	●	●	●		
 SEKT 4 Corner 45° Positive (p. 63)	SEKT 1204 (APMX 6mm)	SHL					●	●	●	●	●	●		

CYL : Cylindrical
WEL : Weldon Shank
SHL : Shell Mill
MOD : Modular

Copy Mill		Diameter												Application
		Type	16	20	25	32	40	50	63	80	100	125	160	
 RDKT Round Positive (p. 55)	RDKT 0802 RDKW 0802 (APMX 4mm)	CYL	●	●	●									
		MOD	●	●	●									
	RDKT 10T3 RDKW 10T3 (APMX 5mm)	CYL		●	●									
		SHL					●	●						
		MOD		●	●									
	RDKT 1204 RDKW 1204 (APMX 6mm)	CYL			●	●								
		SHL					●	●	●					
		MOD			●	●								

CYL : Cylindrical
WEL : Weldon Shank
SHL : Shell Mill
MOD : Modular



Milling Inserts Overview

A 2 Corner	 Positive	APKT +Cutters	APKT 1003, 1604	p. 44
		APMT +Cutters	APMT 1135, 1604	p. 46
		ADKT	ADKT 1505	p. 48
		AOMT	AOMT 1236	p. 49
O Octagon	 Positive	ODMT +Cutters	ODMT 0605 ODMW 0605	p. 50
		OFER	OFER 0704	p. 52
		OFMT	OFMT 05T3	
	 Negative	ONMU	ONMU 0806	p. 53
R Round	 Positive	RDKT +Cutters	RDKT 0802, 10T3, 1204 RDKW 0802, 10T3, 1204	p. 54
		RDKW	RDKW 0501, 0702	p. 56
		RPMT	RPMT 08T2, 10T3, 1204 RPMW 1003, 1204	
S Square	 High Feed	SDMT / SDMW	SDMT 1204, SDMW 1204	p. 59
	 Positive	SDKN (45°)	SDKN 1203, 1504	p. 58
		SEKN / SEKR (45°)	SEKN / SEKR (45°)	p. 60
		SEKT 12T3	SEKT 12T3	p. 61
		SEKT +Cutters	SEKT 1204	p. 62
		SPKN/SPKR (75°)	SPKN 1203, 1504 SPKR 1203	p. 64
		SPUN	SPUN 1203	
	 Negative	SNMX	SNMX1206	p. 65
T Triangle	 ISO	TPKN / TPKR (90°)	TPKN 1603, 2204 TPKR 1603, 2204	p. 66
		TPUN	TPUN 160308	

Milling Grade and Chipbreakers

Milling Grades

Milling Grades	P Steel				M Stainless Steel				K Cast Iron				N Non Ferrous				S Super Alloy			
	P05	P15	P25	P35	M05	M15	M25	M35	K05	K15	K25	K35	N05	N15	N25	N35	S05	S15	S25	S35
PVD	YG602				YG200															
	602				602				602				200				602			


YG602 P20 - P35 M20 - M40 K20 - K40 S15 - S25	 PVD - TiAlN	Universal grade for General Milling Application • Ultra Dense PVD Coating with optimal thermal resistance & strength • Sub-Micron substrate designed for demanding application
YG200 N05 - N35	 PVD - CrN	Optimized grade for Aluminum • Sub-Micron substrate designed for Aluminum application • With unique PVD coating

Milling Chipbreakers

P	M	K	N	S	H			
			N			-AL		• For Aluminum • Very Sharp Geometry
	M			S		-ST		• For Stainless Steel, Super Alloy • Sharp Geometry
P	M	K				General Inserts (No Description)		• First Choice for General Application
P		K				-TR		• For Hardened Steels • Reinforced Geometry
P		K			H	...W / ...N		• For Hardened Material and Cast Irons

Milling - Inserts

APKT 10, 16 - 2 Corner Positive



Series	LE	IC	S
APKT 1003	9.9	6.7	3.6
APKT 1604	15.2	9.4	5.3

● : Stock item ○ : Order made item

APKT	Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
APKT General	APKT 100305 PDTR	0.5	0.15~0.24	0.86	●	
	APKT 100308 PDTR	0.8	0.15~0.24	0.9	●	
	APKT 160404 PDTR	0.4	0.15~0.25	1.11	●	
	APKT 160408 PDTR	0.8	0.15~0.30	1.32	●	
	APKT 160412 PDTR	1.2	0.15~0.32	1.13	●	
	APKT 160416 PDTR	1.6	0.15~0.34	1.13	●	
-AL Aluminum	APKT 160424 PDTR	2.4	0.15~0.28	-	●	
	APKT 100305 - AL	0.5	0.07~0.50	0.86		●
-ST Stainless Steel Super Alloy	APKT 160408 - AL	0.8	0.07~0.50	1.32		●
	APKT 100305 - ST	0.5	0.08~0.22	0.86	●	
-TR Hardened Steel	APKT 160408 - ST	0.8	0.08~0.25	1.32	●	
	APKT 160408 - TR	0.8	0.26~0.40	1.32	●	


Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Cutter - Shouldermilling

APKT 10, 16 Shoulder Mill



2 Corner Positive Inserts
Cutting Angle : 90°



Cutters - APKT 10

EDP	Designation	Type	Z	DC	LF	DCON	CBDP	DCFSMS	APMX	(mm)
17000083	E90 - APKT10 - D16Z2C16 - L100	C	2	16	100	16	-	-	9	●
17000085	E90 - APKT10 - D20Z3C20 - L120	C	3	20	120	20	-	-	9	●
17000082	E90 - APKT10 - D16Z2W16 - L85	W	2	16	85	16	-	-	9	●
17000084	E90 - APKT10 - D20Z3W20 - L90	W	3	20	90	20	-	-	9	●
17000087	F90 - APKT10 - D40Z4S16	S	4	40	40	16	18	34	9	●
17000088	F90 - APKT10 - D50Z7S22	S	7	50	40	22	20	42	9	●


Screw : TP072505 (DC < 20Φ) / TP072506 (20Φ ≤ DC) Wrench : TPWFTP07

Cutters - APKT 16

EDP	Designation	Type	Z	DC	LF	DCON	CBDP	DCFSMS	APMX	(mm)
17000091	E90 - APKT16 - D25Z2C20 - L100	C	2	25	100	20	-	-	14	●
17000094	E90 - APKT16 - D32Z3C25 - L110	C	3	32	110	25	-	-	14	●
17000092	E90 - APKT16 - D25Z2W25 - L110	W	2	25	110	25	-	-	14	●
17000093	E90 - APKT16 - D32Z3W25 - L110	W	3	32	110	25	-	-	14	●
17000095	F90 - APKT16 - D50Z5S22	S	5	50	40	22	20	45	14	●
17000096	F90 - APKT16 - D63Z6S22	S	6	63	40	22	20	50	14	●
17000097	F90 - APKT16 - D80Z7S27	S	7	80	50	27	23	56	14	●

Screw : TP154008 Wrench : TPWFTP15

Milling - Inserts
APMT 11, 16 - 2 Corner Positive




Series	LE	IC	S
APMT 1135	9.5	6.2	3.5
APMT 1604	14.6	9.2	4.76

● : Stock item ○ : Order made item


APMT	Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
	APMT 113504 PDTR	0.4	0.15~0.22	1.26	●	
	APMT 113508 PDTR	0.8	0.15~0.25	1.07	●	
	APMT 160408 PDTR	0.8	0.16~0.30	1.11	●	

APMT
General

Milling - Cutter - Shouldermilling
APMT 11, 16 Shoulder Mill



2 Corner Positive Inserts
Cutting Angle : 90°



Cutters - APMT 11

EDP	Designation	Type	Z	DC	LF	DCON	CBDP	DCFSMS	APMX	(mm)
17000102	E90 - APMT11 - D16Z2C16 - L120	C	2	16	120	16	-	-	9	●
17000103	E90 - APMT11 - D20Z2C20 - L120	C	2	20	120	20	-	-	9	●
17000104	E90 - APMT11 - D25Z4C25 - L150	C	4	25	150	25	-	-	9	●
17000105	E90 - APMT11 - D32Z4W25 - L110	W	4	32	110	25	-	-	9	●

Screw : TP072506 Wrench : TPWFTP07


Cutters - APMT 16

EDP	Designation	Type	Z	DC	LF	DCON	CBDP	DCFSMS	APMX	(mm)
17000107	E90 - APMT16 - D25Z2C25 - L120	C	2	25	120	25	-	-	14	●
17000108	E90 - APMT16 - D32Z3W32 - L110	W	3	32	110	32	-	-	14	●
17000109	F90 - APMT16 - D50Z5S22	S	5	50	40	22	20	42	14	●
17000110	F90 - APMT16 - D63Z6S22	S	6	63	40	22	20	50	14	●
17000111	F90 - APMT16 - D80Z7S27	S	7	80	50	27	23	56	14	●

Screw : TP154008 Wrench : TPWFTP15

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Inserts
ADKT - 2 Corner Positive




Series	LE	IC	S
ADKT 1505	13.7	9.7	5.8

● : Stock item ○ : Order made item

ADKT		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
ADKT General		ADKT 150508 PDTR	0.8	0.16~0.30	1.87	●	

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Inserts
AOMT - 2 Corner Positive




Series	LE	IC	S
AOMT 1236	10.5	6.6	3.6

● : Stock item ○ : Order made item

AOMT		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
AOMT General		AOMT 123604 PDTR	0.4	0.08~0.22	1.07	●	
		AOMT 123608 PDTR	0.8	0.08~0.24	0.91	●	

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Inserts
ODMT / ODMW - 8 Corner Positive




Series	IC	S
ODMT0605	15.9	5.6

● : Stock item ○ : Order made item


ODMT ODMW		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
ODMT General		ODMT 060508	0.8	0.21~0.35	-	●	
ODMW Hard Materials		ODMW 060508	0.8	0.26~0.40	-	●	

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Cutter - Facemilling
ODMT 06 Facemill



8 Corner Positive Inserts
APMX 3.5mm
Cutting Angle : 43°




Cutters - ODMT 06

EDP	Designation	Type	Z	DC	DCX	LF	DCON	CBDP	DCFSMS	APMX	(mm)
17000001	F43 - ODMT06 - D63Z5S22	S	5	63	73	40	22	20	50	3.5	●
17000002	F43 - ODMT06 - D80Z6S27	S	6	80	90	50	27	23	56	3.5	●
17000003	F43 - ODMT06 - D100Z7S32	S	7	100	110	50	32	26	78	3.5	●
17000004	F43 - ODMT06 - D125Z8S40	S	8	125	135	63	40	28	89	3.5	●

Screw : TP205013 Wrench : TPWFTP20

Milling - Inserts
OFER, OFMT - 8 Corner Positive



Series	IC	S
OFER 0704	18.05	4.78
OFMT 05T3	12.73	4.06


● : Stock item ○ : Order made item

OFER		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
OFER General		OFER 070405	0.5	0.22~0.50	-	●	

OFMT		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
OFMT General		OFMT 05T308	0.8	0.15~0.25	-	●	


Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Inserts
ONMU - 16 Corner Negative



Series	IC	S
ONMU 0806	20.2	5.8


● : Stock item ○ : Order made item

ONMU		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
ONMU General		ONMU 080608	0.8	0.22~0.50	-	●	

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Inserts

RDKT - Round Inserts



Series	INSD	S
RDK□0501	5	1.4
RDK□0702	7	2.4
RDK□0802	8	2.4
RDK□10T3	10	4.0
RDK□1204	12	4.8

● : Stock item ○ : Order made item

RDKT	Designation	Fz (mm/tooth)	YG602	YG200
RDKT General	RDKT 0802M0	0.15~0.25	●	
	RDKT 10T3M0	0.15~0.28	●	
	RDKT 1204M0	0.20~0.30	●	
-ST Stainless Steel Super Alloy	RDKT 0802M0 - ST	0.08~0.25	●	
	RDKT 10T3M0 - ST	0.08~0.28	●	
	RDKT 1204M0 - ST	0.10~0.30	●	
-TR Hardened Steel	RDKT 0802M0 - TR	0.18~0.35	●	
	RDKT 10T3M0 - TR	0.22~0.40	●	
	RDKT 1204M0 - TR	0.22~0.40	●	
RDKW Hard Materials	RDKW 0501M0	0.10~0.20	●	
	RDKW 0702M0	0.12~0.25	●	
	RDKW 0802M0	0.13~0.25	●	
	RDKW 10T3M0	0.16~0.30	●	
	RDKW 1204M0	0.16~0.35	●	


Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Cutter - Copymilling

RDKT 08, 10, 12 Copymill



Round Positive Inserts



Cutters - RDKT 08

EDP	Designation	Type	Z	DC	DCX	LF	DCON	CBDP	DCFSMS	APMX	
17000005	E - RDKT08 - D16Z2C16 - L160	C	2	8	16	160	16	-	-	4	●
17000007	E - RDKT08 - D20Z2C20 - L180	C	2	12	20	180	20	-	-	4	●
17000009	E - RDKT08 - D25Z3C20 - L180	C	3	17	25	180	20	-	-	4	●
17000010	M - RDKT08 - D16Z2M08	M	2	8	16	23	M08	-	13	4	●
17000011	M - RDKT08 - D20Z2M10	M	2	12	20	30	M10	-	18	4	●
17000012	M - RDKT08 - D25Z3M12	M	3	17	25	35	M12	-	21	4	●

Screw : TP082505 Wrench : TPWFTP08

Cutters - RDKT 10

EDP	Designation	Type	Z	DC	DCX	LF	DCON	CBDP	DCFSMS	APMX	
17000013	E - RDKT10 - D20Z2C20 - L180	C	2	10	20	180	20	-	-	5	●
17000015	E - RDKT10 - D25Z2C25 - L180	C	2	15	25	180	25	-	-	5	●
17000019	F - RDKT10 - D40Z5S16	S	5	30	40	40	16	18	34	5	●
17000020	F - RDKT10 - D50Z6S22	S	6	40	50	50	22	22	42	5	●
17000017	M - RDKT10 - D20Z2M10	M	2	10	20	30	M10	-	18	5	●
17000018	M - RDKT10 - D25Z3M12	M	3	15	25	35	M12	-	21	5	●


Screw : TP154008RD Wrench : TPWFTP15

Cutters - RDKT 12

EDP	Designation	Type	Z	DC	DCX	LF	DCON	CBDP	DCFSMS	APMX	
17000021	E - RDKT12 - D25Z2C25 - L180	C	2	13	25	180	25	-	-	6	●
17000023	E - RDKT12 - D32Z2C32 - L200	C	2	20	32	200	32	-	-	6	●
17000024	E - RDKT12 - D32Z3C32 - L160	C	3	20	32	160	32	-	-	6	●
17000028	F - RDKT12 - D40Z4S16	S	4	28	40	40	16	18	34	6	●
17000029	F - RDKT12 - D50Z5S22	S	5	38	50	50	22	22	42	6	●
17000030	F - RDKT12 - D63Z6S22	S	6	51	63	50	22	20	48	6	●
17000026	M - RDKT12 - D25Z2M12	M	2	13	25	35	M12	-	21	6	●
17000027	M - RDKT12 - D32Z3M16	M	3	20	32	42	M16	-	29	6	●

Screw : TP154009 Clamp : TP153507 Wrench : TPWFTP15

Milling - Inserts
RPMT - Round Inserts




Series	INSD	S
RPMT 08T2	8	2.78
RPMT 10T3	10	3.97
RPMT 1204	12	4.76

● : Stock item ○ : Order made item

RPMT		Designation	Fz (mm/tooth)	YG602	YG200
RPMT General		RPMT 08T2M0	0.10~0.24	●	
		RPMT 10T3M0	0.16~0.30	●	
		RPMT 1204M0	0.20~0.35	●	
-ST Stainless Steel Super Alloy		RPMT 1204M0 - ST	0.10~0.30	●	

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Inserts
RPMW - Round Inserts




Series	INSD	S
RPMW 1003	10	3.18
RPMW 1204	12	4.76

● : Stock item ○ : Order made item

RPMW		Designation	Fz (mm/tooth)	YG602	YG200
RPMW Hard Materials		RPMW 1003M0	0.16~0.30	●	
		RPMW 1204M0	0.16~0.35	●	

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Inserts
SDKN - 4 Corner Square ISO



Series	AS	IC	S
SDK□1203	15°	12.7	3.1
SDK□1504	15°	15.88	4.7
SEK□1203	20°	12.7	3.2


● : Stock item ○ : Order made item

SDKN	Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
 SDKN Hard Materials	SDKN 1203 AETN	0.5	0.22~0.35	1.85	●	
	SDKN 1203 AETN -PW	0.4	0.22~0.35	1.98	●	
	SDKN 1504 AETN	0.45	0.22~0.40	2	●	
	SDKN 1504 AETN - PW	0.4	0.22~0.40	1.95	●	

- PW : for improved surface roughness

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Inserts
SDMT / W - 4 Corner Square High Feed




Series	IC	S
SDM□1204	12.7	4.7

● : Stock item ○ : Order made item

SDMT SDMW	Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
 -ST Stainless Steel Super Alloy	SDMT 120420 -ST	1.9	0.60~1.20	1.45	○	
 SDMW Hard Materials	SDMW 120420	1.9	0.60~1.40	1.4	○	

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Inserts
SEKR / N - 4 Corner Square ISO



Series	AS	IC	S
SDK□1203	15°	12.7	3.1
SDK□1504	15°	15.88	4.7
SEK□1203	20°	12.7	3.2


● : Stock item ○ : Order made item

SEKR SEKN		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
SEKR General		SEKR 1203 AFTN	0.4	0.14~0.30	1.4	●	
		SEKR 1203 AFTN - PW	0.4	0.14~0.30	1.4	●	
SEKN Hard Materials		SEKN 1203 AFTN	0.4	0.22~0.35	1.4	●	
		SEKN 1203 AFTN - PW	0.4	0.23~0.35	1.4	●	

- PW : for improved surface roughness

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Inserts
SEKT 12T3 - 4 Corner Positive




Series	IC	S
SEKT 12T3	13.4	4

● : Stock item ○ : Order made item

SEKT 12T3		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
SEKT 12T3 General		SEKT 12T3 AGTN	1.5	0.15~0.30	1.3	●	
-AL Aluminum		SEKT 12T3 - AL	1.5	0.07~0.55	1.3		●
-ST Stainless Steel Super Alloy		SEKT 12T3 - ST	1.5	0.08~0.30	1.3	●	

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Inserts
SEKT 1204 - 4 Corner Positive



Series	IC	S
SEKT 1204	12.7	4.9

● : Stock item ○ : Order made item


SEKT 1204		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
SEKT 1204 General		SEKT 1204 AFTN	1.1	0.20~0.35	1.18	●	
-AL Aluminum		SEKT 1204 - AL	1.1	0.07~0.55	1.18		●
-ST Stainless Steel Super Alloy		SEKT 1204 - ST	1.1	0.08~0.30	1.18	●	

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Cutter - Facemilling
SEKT 1204 Facemill



4 Corner Positive Inserts
APMX 6mm
Cutting Angle : 45°




Cutters - SEKT 1204

EDP	Designation	Type	Z	DC	DCX	LF	DCON	CBDP	DCFSMS	APMX	(mm)
17000031	F45 - SEKT12 - D40Z4S16	S	4	40	54	40	16	18	32	6	●
17000032	F45 - SEKT12 - D50Z5S22	S	5	50	64	40	22	20	48	6	●
17000033	F45 - SEKT12 - D63Z4S22	S	4	63	77	40	22	20	50	6	●
17000034	F45 - SEKT12 - D63Z6S22	S	6	63	77	40	22	20	50	6	●
17000035	F45 - SEKT12 - D80Z4S27	S	4	80	94	50	27	22	56	6	●
17000036	F45 - SEKT12 - D80Z7S27	S	7	80	94	50	27	22	56	6	●
17000037	F45 - SEKT12 - D100Z8S32	S	8	100	114	50	32	25	78	6	●
17000038	F45 - SEKT12 - D125Z10S40	S	10	125	139	63	40	29	90	6	●
17000039	F45 - SEKT12 - D160Z12S40	S	12	160	174	63	40	30	114	6	×


Screw : TP204510 Wrench : TPWFTP20

Milling - Inserts
SPKN / R, SPUN - 4 Corner Square ISO



Series	KRINS	AS	IC	S
SPK□1203	75°	11°	12.7	3.2
SPK□1504	75°	11°	15.88	4.8
SPUN 1203	-	11°	12.7	3.2

● : Stock item ○ : Order made item


SPKR SPKN		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
SPKR General		SPKR 1203 EDTR	0.8	0.15~0.35	1.4	●	
		SPKR 1203 EDTR - PW	0.8	0.15~0.35	1.4	●	
SPKN Hard Materials		SPKN 1203 EDTR	0.8	0.16~0.34	1.4	●	
		SPKN 1203 EDTR - PW	0.8	0.20~0.35	1.4	●	
		SPKN 1504 EDTR	-	0.15~0.34	1.3	●	
		SPKN 1504 EDTR - PW	-	0.25~0.40	1.3	●	

- PW : for improved surface roughness

SPUN		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
SPUN		SPUN 120308	0.8	-	-	●	


Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Inserts
SNMX - 8 Corner Negative




Series	IC	S
SNMX 1206	12.7	6.25

● : Stock item ○ : Order made item

SNMX		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
SNMX General		SNMX 1206 ANN	0.8	0.16~0.34	1.7	●	

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-

Milling - Inserts
TPKR / N, TPUN - 3 Corner ISO



Series	KRINS	IC	S
TPK□1603	90°	9.53	3.18
TPK□2204	90°	12.7	4.76
TPUN 1603	-	9.53	3.18


● : Stock item ○ : Order made item

TPKR TPKN		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
TPKR General		TPKR 1603 PDTR	-	0.15~0.28	1.2	●	
		TPKR 1603 PDTR - PW	-	0.15~0.28	1.2	●	
		TPKR 2204 PDTR	-	0.18~0.35	1.7	●	
		TPKR 2204 PDTR - PW	-	0.18~0.35	1.7	●	
TPKN Hard Materials		TPKN 1603 PDTR	-	0.15~0.30	1.2	●	
		TPKN 1603 PDTR - PW	-	0.20~0.35	1.2	●	
		TPKN 2204 PDTR	-	0.17~0.30	1.7	●	
		TPKN 2204 PDTR - PW	-	0.24~0.40	1.7	●	

- PW : for improved surface roughness

TPUN		Designation	RE (mm)	Fz (mm/tooth)	BS (mm)	YG602	YG200
TPUN		TPUN 160308	0.8	-	-	●	

Cutting Speed			Vc (m/min.)			
ISO	VDI	Sub Group	YG602		YG200	
			Min.	Max.	Min.	Max.
P	1~5	Non Alloy Steel	140	240	-	-
	6~9	Low Alloy Steel	120	220	-	-
	10~11	High Alloy Steel	70	150	-	-
M	12~13	Ferritic & Martensitic	120	200	-	-
	14	Austenitic Stainless Steel	140	250	-	-
K	15~16	Grey Cast Iron	140	220	-	-
	17~18	Nodular Cast Iron	150	240	-	-
N	21~30	Aluminum	-	-	300	800
S	31~37	Heat Resistant Super Alloy	25	45	-	-
H	38~41	Hardened Material	40	80	-	-



Drilling Overview


Drilling Grades

Drilling Grades		P Steel				M Stainless Steel				K Cast Iron			
		P05	P15	P25	P35	M05	M15	M25	M35	K05	K15	K25	K35
PVD	YG602			602				602				602	

YG602

P20 - P35M20 - M40K20 - K40S15 - S25


PVD - TiAlN



Universal grade for General Drilling Application

- Ultra Dense PVD Coating with optimal thermal resistance & strength
- Sub-Micron substrate designed for demanding application


Universal Drilling Inserts

	4 Corner	SPMX Series	SPMX	05, 06, 07, 09, 11, 14
	ISO 3 Corner	WCMX Series	WCMX	04, 05, 06, 08

Drilling Chipbreakers

P	M	K			
	M		-ST		• Sharp Geometry • Sticky Material, Stainless Steel
P	M	K	General Inserts (No Description)		• First Choice for General Application

Drilling - Inserts
Drilling Inserts (SPMX)




Series	IC	S
SPMX 050204	5.00	2.38
SPMX 060204	6.00	2.41
SPMX 07T308	7.94	3.97
SPMX 090408	9.80	4.30
SPMX 110408	11.50	4.90
SPMX 140512	14.30	5.30


SPMX	Designation	Fn (mm/rev.)	YG602
SPMX General 	SPMX 050204	0.07~0.14	●
	SPMX 060204	0.08~0.14	●
	SPMX 07T308	0.08~0.16	●
	SPMX 090408	0.08~0.16	●
	SPMX 110408	0.1~0.18	●
	SPMX 140512	0.1~0.2	●
-ST Stainless Steel 	SPMX 050204 - ST	0.03~0.1	●
	SPMX 060204 - ST	0.04~0.11	●
	SPMX 07T308 - ST	0.04~0.11	●
	SPMX 090408 - ST	0.05~0.12	●

Cutting Speed			Vc (m/min.)	
ISO	VDI	Sub Group	YG602	
			Min.	Max.
P	1~5	Non Alloy Steel	140	240
	6~9	Low Alloy Steel	120	220
	10~11	High Alloy Steel	70	150
M	12~13	Ferritic & Martensitic	120	200
	14	Austenitic Stainless Steel	140	250
K	15~16	Grey Cast Iron	140	220
	17~18	Nodular Cast Iron	150	240


Drilling - Inserts
Drilling Inserts (WCMX)



Series	IC	S
WCMX 040208	6.35	2.38
WCMX 050308	7.94	3.18
WCMX 06T308	9.53	3.97
WCMX 080412	12.70	4.76

WCMX	Designation	Fn (mm/rev.)	YG602
WCMX General 	WCMX 040208	0.05~0.11	●
	WCMX 050308	0.06~0.14	●
	WCMX 06T308	0.08~0.14	●
	WCMX 080412	0.08~0.14	●

Compatible Screw for WCMX

Screw Image	Insert	Thread M	Length L	Head Diameter D	Head Angle θ	Torx Screw
	WCMX 06	M3.5	7.4	4.8	60	Torx Plus 15
	WCMX 08	M4	9.4	5.6	60	Torx Plus 15

Cutting Speed			Vc (m/min.)	
ISO	VDI	Sub Group	YG602	
			Min.	Max.
P	1~5	Non Alloy Steel	140	240
	6~9	Low Alloy Steel	120	220
	10~11	High Alloy Steel	70	150
M	12~13	Ferritic & Martensitic	120	200
	14	Austenitic Stainless Steel	140	250
K	15~16	Grey Cast Iron	140	220
	17~18	Nodular Cast Iron	150	240



Technical Information - Comparison Chart

Comparison Chart - Turning Grades

ISO	YG	Sandvik	Iscar	Kenna metal	Seco	Walter	Mitsu bishi	Kyocera	Tungaloy	Sumi tomo	Taegutec	Korloy	Duracarb
P10	YG3010	GC4305 GC4205 GC4315 GC4215	IC8005 IC428 IC8150 IC9015	KCP05 KC9105 KCP10 KC9110	TP0501 TP0500 TP1501 TP1500	WPP01 WPP05S WPP10S	UE6105 MC6015 UE6110	CA5505 CA510 CA515 CA5515	T9105 T9115	AC8015P AC810P	TT8115	NC3010 NC3215	DC9015
P20	YG3020 YG801	GC4325 GC4225	IC8250 IC9015	KCP25 KC9125	TP2501 TP2500	WPP20S	MC6025 UE6020	CA525 CA5525	T9125	AC8025P AC820P	TT8125	NC3220 NC3225 NC3120	DC9025
P30	YG801 YG3030	GC4335 GC4235	IC8350 IC8025	KCP30 KC9140	TP3501 TP3500	WPP30S	MC6035 UE6035 VP15TF	CA530 CA5535 CR9025	T9135	AC8035P AC830P AC630M	TT5100 TT8135	NC3030 NC5330 PC3545	DC9025 DC8035
M10	YG801	GC2015 GC1105 GC1115	IC807 IC8025 IC907	KCM15 KC5510 KCU10	TS2000	WSM10S	US7020 US905 VP05RT VP10RT	CA6515 PR915 PR1025 PR1215	T6120	AC610M AC6020M AC510U	TT9215 TT5080	NC9020 PC8110	DC610
M20	YG801	GC2025 GC1115	IC808 IC8080 IC908	KCM25 KC5525 KCU25 KC5020	TT2501 TP2000 TM2000 TS2500	WMP20S WSM20S WSM21	US7020 VP20MF UP20M	CA6525 PR915 PR1125 PR1225	T6130	AC6020M AC6030M AC520U	TT9225 TT9080	PC5300 PC8115	
M30	YG3030	GC2035	IC830 IC928	KCM35 KC9240	TP3500 TM4000	WSM30S	UC735 VP15TF VP20MF	PR1125 PR1535	T6130	AC6030M AC6040M AC630M AC530U	TT9235 TT8020	NC9025 PC9030	DC8035
K05	YG1001	GC3205	IC5005	KCK05	TK1001 TK1000	WKK10S	MC5005 UC5105	CA4505 CA4010	T5105	AC405K	TT7005	NC6205	DC820 DC610
K10	YG1001	GC3210	IC5010 IC5100	KCK15	TK1001 TK1000	WKK10S	MC5015 UC5115	CA4515 CA4115	T515	AC415K	TT7310 TT7015	NC6210	
K15	YG3010	GC3215	IC8150	KCK20	TK2001 TK2000	WKK20S WKP30S	UE6110 VP15TF	CA4120	T5125	AC420K	TT6300	NC6215	

Technical Information - Comparison Chart

Comparison Chart - Turning Chipbreakers

Negative Inserts

Material	YG	Sandvik	Iscar	Kenna metal	Seco	Walter	Mitsu bishi	Kyocera	Tungaloy	Sumi tomo	Taegutec	Korloy	Duracarb
STEEL	UF	PF	F3P NF	FF FN	F1 MF2	FP5	FH LP	GP PP	TF	FL SP	FG FA	VF HU	41
	UL		PP NF			FP5	FY SY	CQ VF	TSF	LU	FC FT	HC	43
	UM		TF	MN	M3	MP3	MP	HS	TM	GU UX	MC PC	VM GM	46
	UG	PM	GN M3P	MN	M3 MR3	MP5	MP,MA	PS	TM	UG	MT PC	GR HR	45
	UC	PR	NR	MP RP	MR4	RP5	Standard	Standard	TH	UZ	MG-	B25	53
	UR	PR	NR R3P	UN RN MG-	MR3 MR6	RP7	RP MH RK	PT PH	THS	ME MU	RT	GR	
STAINLESS STEEL	MM	MM	M3M	MG-MP	MR3	NM4	MM	MS	SM	GU	EM ET	GS	42
CAST IRON	UC	PR	NR	MP RP	MR4	MK5	Standard	Standard	All Round	UZ	MG-	B25	53
	UR	PR	NR R3P	UN RN MG-	MR3 MR6	RK5 RK7	RP MH RK	PT PH	CH	ME MU	RT	GR	
	..MA			RP	MR7	..MA	MG-	C	CH	GZ	..MA		53

Positive Inserts

Material	YG	Sandvik	Iscar	Kenna metal	Seco	Walter	Mitsu bishi	Kyocera	Tungaloy	Sumi tomo	Taegutec	Korloy	Duracarb
STEEL	UF	PF	PF	LF UF	MF2	PF2 FP4	FM LM LP	GQ PP	01 PSF	FP	FG	HFP	41
	UG	PM		MF	MF3	MP4 FP6	MP Standard MM MV	HQ	PS PM	MU	MT	C25	51
STAINLESS STEEL	UF	PF	PF	LF	MF2	MM4 PS5	FM LM LP	GQ PP	PM	FP	FG	HFP	41
CAST IRON	UG	PM		UF	MF3	MK4 RK4	MP Standard MM MV	HQ	CM	MU	MT	C25	51
ALUMINUM	AL		AS	MF	AL	PF2 PM2	AZ	CF CK	AL	AG	FL	AK	AU



HIGH QUALITY PRODUCTS and ON TIME DELIVERY for WORLD-WIDE CUSTOMERS

Since 1982, YG-1 has been committed to quality, innovation and the unique customer experience. Our performance and experience have granted YG-1 the global impression of one of the leading manufacturers of high quality cutting tool solutions. This global footprint expands over 75 countries, with international logistic centers, pledging to our customers to give the best service available today - and tomorrow.

EUROPE

BELGIUM	FINLAND	ITALY	PORTUGAL	SLOVENIA	THE NETHERLANDS
CROATIA	FRANCE	LITHUANIA	ROMANIA	SPAIN	TURKEY
CZECH REPUBLIC	GERMANY	NORWAY	RUSSIA	SWEDEN	UNITED KINGDOM
DENMARK	HUNGARY	POLAND	SERBIA	SWITZERLAND	

ASIA PACIFIC

AUSTRALIA	INDONESIA	KINGDOM OF SAUDI ARABIA	SINGAPORE	UNITED ARAB EMIRATES
CHINA	IRAN	MALAYSIA	SOUTH KOREA	VIETNAM
HONG KONG	ISRAEL	PAKISTAN	TAIWAN	
INDIA	JAPAN	PHILIPPINES	THAILAND	

AMERICAS

BRAZIL	CANADA	COLOMBIA	MEXICO	UNITED STATES
--------	--------	----------	--------	---------------

AFRICA

EGYPT	SOUTH AFRICA
-------	--------------